

SAFETY DATA SHEET

Fluid Film Spray Svart

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Fluid Film Spray Svart

Product no.

ffssvart

Unique formula identifier (UFI)

QCS2-EYH3-TG4A-D5PR

1.2. Relevant identified uses of the substance or mixture and uses advised against

▼ Relevant identified uses of the substance or mixture

Corrosion Inhibitor, Lubricant, Rust remover, Electro spray, Paint

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Rettedal Bilkontroll AS

Næringsveien 6

4323 SANDNES

Norway

0047 51 65 11 51

Contact person

www.fluidfilm.no

E-mail

post@fluidfilm.no

Revision

19/02/2026

SDS Version

3.0

Date of previous version

14/02/2024 (2.0)

1.4. Emergency telephone number

In urgent situations: Call 112 and request the poison information centre. (24h service)

In less severe situations: Call 010-456 6700 (24h service)

See also section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP).

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

This product is an aerosol dispenser where the propellant is separated from the product upon spraying. As a result, the concentrations of the propellants are not considered for the classification of the mixture in regard of health and environment.

2.2. Label elements

Hazard pictogram(s)

**Signal word**

Danger

Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)

Precautionary statement(s)**General**

Keep out of reach of children. (P102)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Do not spray on an open flame or other ignition source. (P211)

Do not pierce or burn, even after use. (P251)

▼ Response

Not applicable.

▼ Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

▼ Disposal

Dispose of contents/container in accordance with local regulation. (P501)

▼ Hazardous substances

Does not contain any substances required to report

Additional labelling

UFI: QCS2-EYH3-TG4A-D5PR

2.3. Other hazards**▼ Additional warnings**

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum), hydrotreated heavy paraffinic (<3% DMSO)	CAS No.: 64742-54-7 EC No.: 265-157-1 REACH: Index No.: 649-467-00-8	50-70%		[19]
Butane	CAS No.: 106-97-8 EC No.: 203-448-7 REACH: 01-2119474691-32 Index No.: 601-004-00-0	10-15%	Flam. Gas 1A, H220 Press. Gas (Liq.), H280	[16]
Isobutane	CAS No.: 75-28-5 EC No.: 200-857-2 REACH: 01-2119485395-27 Index No.: 601-004-00-0	5-10%	Flam. Gas 1A, H220 Press. Gas (Liq.), H280	[16]
Propane.	CAS No.: 74-98-6 EC No.: 200-827-9 REACH: 01-2119486944-21 Index No.: 601-003-00-5	5-10%	Flam. Gas 1A, H220 Press. Gas (Liq.), H280	[16]

Benzenesulfonic acid, di-C10-18-alkyl derivs., calcium salts	CAS No.: 93820-57-6 EC No.: 298-637-4 REACH: Index No.:	1-3%	Eye Irrit. 2, H319	[19]
--	--	------	--------------------	------

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[16] Propellant

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

None known.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container. In a fire or if heated, a pressure increase will occur and the container may burst.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. ▼ Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 112, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Accidental releases always pose a serious risk of fire or explosion.

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. ▼ Precautions for safe handling

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

Recommended storage material

Keep only in original packaging.

Storage conditions

Aerosols: Do not expose to direct sunlight or temperatures above 50 ° C.

Do not expose to heat, hot surfaces, sparks, open flames or other sources of ignition. Smoking forbidden.

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. ▼ Control parameters

Distillates (petroleum), hydrotreated heavy paraffinic (<3% DMSO)

Short term exposure limit (15 minutes) (mg/m³): 3 (oljedimma (inklusive oljerök))

Long term exposure limit (8 hours) (mg/m³): 1 (oljedimma (inklusive oljerök))

Annotations:

V = Indicative short term limit.

Butane

Short term exposure limit (15 minutes) (mg/m³): 500

Long term exposure limit (8 hours) (mg/m³): 350

Annotations:

V = Indicative short term limit.

10 = The limit value refers to hydrocarbons in vapor form, i.e. up to 12 carbon atoms. In the case of exposure to hydrocarbons with more than 12 carbon atoms that occur in the form of aerosol, particles or liquid droplets, the limit value for organic dust and mist, 5 mg/m³, is applied. The limit value does not apply to white spirit, which has its own limit values.

Isobutane

Short term exposure limit (15 minutes) (mg/m³): 500

Long term exposure limit (8 hours) (mg/m³): 350

Annotations:

V = Indicative short term limit.

10 = The limit value refers to hydrocarbons in vapor form, i.e. up to 12 carbon atoms. In the case of exposure to hydrocarbons with more than 12 carbon atoms that occur in the form of aerosol, particles or liquid droplets, the limit value for organic dust and mist, 5 mg/m³, is applied. The limit value does not apply to white spirit, which has its own limit values.

Propane.

Short term exposure limit (15 minutes) (mg/m³): 500

Long term exposure limit (8 hours) (mg/m³): 350

Annotations:

V = Indicative short term limit.

10 = The limit value refers to hydrocarbons in vapor form, i.e. up to 12 carbon atoms. In the case of exposure to hydrocarbons with more than 12 carbon atoms that occur in the form of aerosol, particles or liquid droplets, the limit value for organic dust and mist, 5 mg/m³, is applied. The limit value does not apply to white spirit, which has its own limit values.

The Swedish Work Environment Authority's regulations and general guideline (AFS 2023:14) on limit values for respiratory exposure in the work environment.

DNEL

No data available.

PNEC

No data available.

8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

▼ Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure


No specific requirements.

Individual protection measures, such as personal protective equipment


Generally

Use only CE marked protective equipment.



Respiratory Equipment

Work situation	Type	Class	Colour	Standards	
In case of inadequate ventilation	Combination filter AXP1		Brown/White	EN14387, EN143	


Skin protection

Work situation	Recommended	Type/Category	Standards	
When there is risk of splash- / intermittent exposure	Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester.	-	-	

▼ Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.4	> 480	EN374-2, EN16523-1, EN388	
Neoprene (Neoprene)	0,6	> 480	EN374-2, EN16523-1, EN388	

Eye protection

Work situation	Type	Standards	
When there is risk of splash- / intermittent exposure	Safety glasses with side shields.	EN166	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Aerosol

Colour

Black

Odour / Odour threshold

Lanolin

▼ pH

Not applicable - product is a gas

Density (g/cm³)

0.76

▼ Kinematic viscosity

No data available.

▼ Particle characteristics

No data available.

Phase changes

▼ Melting point/Freezing point (°C)

No data available.

Softening point/range (°C)

Does not apply to aerosols.

▼ Boiling point (°C)

No data available.

▼ Vapour pressure

No data available.

▼ Relative vapour density

No data available.

▼ Decomposition temperature (°C)

No data available.

Data on fire and explosion hazards

Flash point (°C)

Does not apply to aerosols.

Flammability (°C)

The material is ignitable.

▼ Auto-ignition temperature (°C)

No data available.

▼ Lower and upper explosion limit (% v/v)

No data available.

Solubility

▼ Solubility in water

No data available.

▼ n-octanol/water coefficient (LogKow)

No data available.

▼ Solubility in fat (g/L)

No data available.

9.2. Other information

Other physical and chemical parameters

No data available.

▼ Oxidizing properties

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. ▼ Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. ▼ Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

▼ Symptoms related to the physical, chemical and toxicological characteristics

None known.

11.2. Information on other hazards

▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

None known.

SECTION 12: Ecological information

12.1. ▼ Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. ▼ Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. ▼ Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

HP 3 - Flammable

Waste regulation (SFS 2020:614).

EWC code

13 02 05* Mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packing

EWC code

15 01 02 Plastic packaging

15 01 04 Metallic packaging

SECTION 14: Transport information

14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informatio n:
ADR/ADN/RID	UN1950 AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information.
IMDG	UN1950 AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L EmS: F-D S-U See below for additional information.
IATA	UN1950 AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	See below for additional information.

* Packing group

** Environmental hazards

▼ Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR/ADN/RID / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

▼ Restrictions for application

People under the age of 18 shall not work with this product. This does not apply if the working task is:

- performed by young people who have completed upper secondary education or equivalent education for the task or
- included in teaching that is located in a school premises or other place that is specially arranged for teaching, or
- included in supervisor-led internships for young people, or
- of such a nature that the risk of injury is considered to be minimal.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

[Demands for specific education](#)

No specific requirements.

▼ SEVESO - Categories / dangerous substances

P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

▼ REACH, Annex XVII

Butane is subject to REACH restrictions (entry 40).

Isobutane is subject to REACH restrictions (entry 40).

Propane. is subject to REACH restrictions (entry 40).

▼ Product registration number

Norge: 647788

Additional information

Not applicable.

▼ Sources

The Swedish Work Environment Authority's regulations and general guideline (AFS 2023:2) on planning and organizing work environment work - basic obligations for you with employer responsibility

The Swedish Civil Contingencies Agency on aerosol dispensers (MSBFS 2018:1).

The Swedish Civil Contingencies Agency 2015:8 regulations on measures to prevent and limit the consequences of serious chemical accidents.

Waste regulation (SFS 2020:614).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H220, Extremely flammable gas.

H280, Contains gas under pressure; may explode if heated.

H319, Causes serious eye irritation.

▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

Amje

▼ Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: SE-en